



The Name Says It All

Hensley Mfg., Inc
1097 S. State Rd
Davison, MI 48423
(800) 410-6580
WWW.TRAILERSAVER.COM



The Name Says It All

Adaptor for Under Bed Mounting Rails Installation and Operation Guide

Read all instructions thoroughly before installing
the Under Bed Mounting Adaptor.

WARNING
EXCEEDING MAXIMUM CAPACITY
CREATES A SAFETY HAZARD

The TrailerSaver system attaches to 5th wheel trailer and is rated for a maximum pin weight of 4,500 pounds and gross trailer weight of 20,000 pounds (including the load). The towing vehicle and the ball that is attached to the truck frame are both separately rated for maximum pin weight and the gross weight of the trailer (including the load). Refer to the manufacturer of the vehicle and ball for the maximum pin weight and gross weight of your towing vehicle and ball. Do not exceed the maximum of the towing vehicle, ball, or the TrailerSaver hitch.

1 Warranty Provisions

The TrailerSaver Reese under bed Adaptor comes standard with a 1-year warranty on all parts and service performed by Hensley Mfg.

NOTE: IMPORTANT

Hensley Mfg., Inc. is not responsible for and will not compensate for lost time, vacation, or wages if a hitch is inoperable or requires repair.

1.1 What Is Covered

The warranty period begins on the date of purchase. The warranty is limited to the original purchaser of the TrailerSaver adaptor and is non-transferable. This warranty covers repair or replacement to any TrailerSaver part that is defective in materials or workmanship under normal use.

Warranty items must be returned to Hensley Mfg., Inc. for inspection.

Customer is responsible for all freight charges associated with warranty work.

WARNING: EXCEEDING MAXIMUM CAPACITY CREATES A SAFETY HAZARD.

The TrailerSaver Reese under bed mounting adaptor attaches to the truck bed. It is rated for a maximum tongue weight of 4,500 lbs. and a gross weight of the trailer of 20,000 lbs (including the load).

The towing vehicle and other components that attach to the towing vehicle, are separately rated for maximum tongue weight and gross weight of the trailer (including the load).

Refer to the manufacturer of your vehicle and your hitch for the maximum tongue and gross weight of your towing vehicle and hitch.

Do not exceed the maximum capacity of your towing vehicle, your hitch or the TrailerSaver Reese under bed mounting adaptor.

WARNING! Ensure locking arms are closed and locking pins in place before towing!



Set your 5th wheel hitch into the adaptor slots. Insert the leg pins and clips and you're ready to go!

If you need support at any point of your installation, please call 800-410-6580. Hensley representatives are available between 9am and 5:00pm Eastern Time, Monday through Friday.

If you require immediate assistance during off hours or weekends, please follow the prompts for our emergency line. Leave a message and someone will return your call promptly.

1.2 What Is Not Covered

Items added, changed, or modified after the unit left the possession of Hensley Mfg., Inc.
 Any use of the TrailerSaver for rental or other commercial purposes.
 Normal wear and usage, such as fading or discoloration of painted parts.
 Minor imperfections which do not affect the suitability of the TrailerSaver for its intended use.
 Costs incurred as a result of the consumer's request to have repairs performed, or replacement of parts supplied by other than Hensley Mfg., Inc. without proper authorization or notification by Hensley Mfg., Inc.
 This warranty does not apply to or cover any component which has its own warranty by its manufacturer.

WARNING: IMPORTANT EXCEEDING MAXIMUM CAPACITY CREATES A SAFETY HAZARD.

22,000 lb. max - Gross Trailer Weight Rating and
 4,500 lb max pin weight

If you have any warranty-related questions, please contact Hensley Mfg. at (800) 410-6580.

For Warranty Exchanges ship all parts with Return Authorization # to:

Hensley Mfg., Inc. RMA# _____
 378 Industrial Park Lane
 Hardinsburg, KY 40143

Underbed Adapter

2 INSTALLATION

Read instructions thoroughly before starting. Do not exceed the vehicle manufacturer's rated towing capacity. Hensley Mfg. will not be responsible for damage caused by overloading of the tow vehicle.



1. You should already have the mounting system for the Reese under bed hitch installed in your truck.
2. Ensure that the locking arms are in the open position.
3. Carefully lower the adapter unit until the feet are completely inserted in the mounting holes and the plate lies flat on the truck bed.



4. Close the locking arms.



5. Insert locking pin.